

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Restor-A-Finish
MANUFACTURER: Howard Products, Inc.
ADDRESS: 560 Linne Road
Paso Robles, CA 93446
EMERGENCY PHONE: 1-805-227-1000
CHEMTREC PHONE: 1-800-424-9300
FAX PHONE: 1-805-227-1007
PRODUCT USE: Wood Finish Restorer
PREPARED BY: Howard Products, Inc.



HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT(S)</u>	<u>CAS #</u>	<u>Percent</u>
Distillates, hydrotreated heavy paraffinic	64742-54-7	40-60
Isobutyl acetate	110-19-0	5-15
Isopropanol	67-63-0	5-15
Acetone	67-64-1	3-10
Methyl ethyl ketone	78-93-3	3-10
Propanoic acid, 2-methyl-, 2-methylpropyl ester	97-85-8	3-10
Toluene	108-88-3	1-3
Xylene	1330-20-7	1-3
Gilsonite	12002-43-6	0.5-2
Ethyl benzene	100-41-4	0.1-1

SECTION 3: HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING

Flammable liquid - may release vapors that form flammable mixtures at or above the flash point.
Eye and skin irritant. Contains material that may cause cancer. Contains potential teratogens.

POTENTIAL SHORT TERM HEALTH EFFECTS

ROUTES OF EXPOSURE: Eye, Skin contact, Skin absorption, Inhalation, Ingestion

EYES: May cause irritation

SKIN: May cause irritation

INHALATION: May cause respiratory tract irritation

INGESTION: May cause stomach distress, nausea, or vomiting

TARGET ORGANS: Eyes. Skin. Respiratory system.

CHRONIC EFFECTS: Prolonged or repeated exposure can cause drying, defatting and dermatitis.

SIGNS AND SYMPTOMS: Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 4: FIRST AID MEASURES

EYES: Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

SKIN: Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

INGESTION: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

INHALATION: Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.

NOTES TO PHYSICIAN: Symptoms may be delayed.

GENERAL ADVICE: Keep away from sources of ignition. No smoking. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: Flammable by WHMIS/OSHA criteria. Vapors may travel to a source of ignition and flash back. Containers may explode when heated.

EXTINGUISHING MEDIA:

Suitable extinguishing media:

Dry chemical. Foam. Carbon dioxide.

Unsuitable extinguishing media:

DO not use a solid water stream as it may scatter and spread fire.

PROTECTION OF FIREFIGHTERS:

Specific hazards arising from the chemical:

Not available

Protective equipment for the firefighters: Firefighters should wear full protective clothing including self-contained breathing apparatus

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

HAZARDOUS COMBUSTION PRODUCTS: May include and are not limited to: Oxides of carbon.
EXPLOSION DATA:
Sensitivity to mechanical impact: Not available
Sensitivity to static discharge: Not available

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from an upwind of spill/leak.

METHODS FOR CONTAINMENT: Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.

METHODS FOR CLEANING UP: Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labeled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

SECTION 7: HANDLING AND STORAGE

HANDLING: Use good industrial hygiene practices in handling this material.
STORAGE: Keep out of reach of children. Store in a closed container away from heat, sparks, and flame.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS

INGREDIENT(S)

Distillates, hydrotreated heavy paraffinic

EXPOSURE LIMITS

ACGIH-TLV

Not established

OSHA-PEL

Not established

Isobutyl acetate

ACGIH-TLV

TWA: 150 ppm

OSHA-PEL

TWA: 150 ppm

Isopropanol

ACGIH-TLV

TWA: 200 ppm

STEL: 400 ppm

OSHA-PEL

TWA: 400 ppm

Acetone

ACGIH-TLV

TWA: 500 ppm

STEL: 750 ppm

OSHA-PEL

TWA: 1000 ppm

Methyl ethyl ketone

ACGIH-TLV

TWA: 200 ppm

STEL: 300 ppm

OSHA-PEL

TWA: 200 ppm

Propanoic acid, 2-methyl-, 2-methylpropyl ester

ACGIH-TLV

Not established

OSHA-PEL

Not established

Toluene

ACGIH-TLV

TWA: 10 ppm

Skin: 50 ppm

OSHA-PEL

TWA: 200 ppm

Ceiling: 300 ppm

Xylene

ACGIH-TLV

TWA: 100 ppm

STEL: 150 ppm

OSHA-PEL

TWA: 100 ppm

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

Ethyl benzene

ACGIH-TLV
TWA: 100 ppm
STEL: 125 ppm
OSHA-PEL
TWA: 100 ppm

ENGINEERING CONTROLS:

General ventilation normally adequate

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION:

Wear safety glasses with side shields

HAND PROTECTION:

Rubber gloves. Confirm with a reputable supplier first.

SKIN AND BODY PROTECTION:

As required by employer code.

RESPIRATORY PROTECTION:

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

GENERAL HYGIENE CONSIDERATIONS:

Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	Clear to Dark
FORM:	Liquid
ODOR:	Characteristic Aromatic
ODOR THRESHOLD:	Not available
PHYSICAL STATE:	Liquid
pH:	Not available
MELTING POINT:	Not available
FREEZING POINT:	Not available
BOILING POINT:	> 93.33 °C (> 200 °F)
FLASH POINT:	3.88°C (39°F) Tag Closed Cup
POUR POINT:	Not available
EVAPORATION RATE:	< 1 (BuAc=1)
FLAMMABILITY LIMITS IN AIR, LOWER, % BY VOLUME:	Not applicable
FLAMMABILITY LIMITS IN AIR, UPPER, % BY VOLUME:	Not applicable
VAPOR PRESSURE:	51.2 mmHg @20°C
VAPOR DENSITY:	>1
SPECIFIC GRAVITY:	0.87
OCTANOL/WATER COEFFICIENT:	Not available
SOLUBILITY (H₂O):	None
AUTO-IGNITION TEMPERATURE:	Not available
PERCENT VOLATILE:	Not available

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under recommended storage conditions.
CONDITIONS TO AVOID:	Avoid high temperatures. Do not mix with other chemicals.
INCOMPATIBILITY MATERIALS:	Acids. Oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS:	May include and are not limited to: Oxides of carbon.
POSSIBILITY OF HAZARDOUS REACTIONS:	Hazardous polymerization does not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Component analysis - LC50	LC50
Ingredient(s)	
Distillates, hydrotreated heavy paraffinic	2.18 mg/l/4h rat
Isobutyl acetate	8000 ppm rat
Isopropanol	16970 mg/l/4h rat
Acetone	Not available
Methyl ethyl ketone	2000 mg/l/4h rat

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

Propanoic acid, 2-methyl-, 2-methylpropyl ester	6124 mg/l/4h rat
Toluene	12.5 mg/l/4h rat
Xylene	5000 mg/l/4h rat
Component analysis - Oral LD50 Ingredient(s)	LD50
Distillates, hydrotreated heavy paraffinic	5000 mg/kg rat
Isobutyl acetate	13400 mg/kg rat; 4763 mg/kg rabbit
Isopropanol	4396 mg/kg rat
Acetone	5800 mg/kg rat; 5340 mg/kg rabbit; 3000 mg/kg mouse; 2857 mg/kg human
Methyl ethyl ketone	2600 mg/kg rat; 3000 mg/kg mouse
Propanoic acid, 2-methyl-, 2-methylpropyl ester	12800 mg/kg rat
Toluene	636 mg/kg rat
Xylene	4300 mg/kg rat

Effects of acute exposure

Eye	May cause irritation.
Skin	May cause irritation.
Inhalation	May cause respiratory tract irritation.
Ingestion	May cause stomach distress, nausea or vomiting.
Sensitization	Contains a potential skin sensitizer.
Chronic effects	Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity

ACGIH - Threshold Limit Values - Carcinogens

Acetone	67-64-1	A4 - Not Classifiable as a Human Carcinogen
Ethyl benzene	100-41-4	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Isopropanol	67-63-0	A4 - Not Classifiable as a Human Carcinogen
Toluene	108-88-3	A4 - Not Classifiable as a Human Carcinogen
Xylene	1330-20-7	A4 - Not Classifiable as a Human Carcinogen

IARC - Group 2B (Possibly Carcinogenic to Humans)

Ethyl benzene	100-41-4	Monograph 77 [2000]
---------------	----------	---------------------

IARC - Group 3 (Not Classifiable)

Isopropanol	67-63-0	Monograph 71 [1999]; Supplement 7 [1987]; Monograph 15 [1977]
Toluene	108-88-3	Monograph 71 [1999]; Monograph 47 [1989]
Xylene	1330-20-7	Monograph 71 [1999]; Monograph 47 [1989]

U.S. - California - Proposition 65 - Carcinogens List

Ethyl benzene	100-41-4	carcinogen, initial date 6/11/04
---------------	----------	----------------------------------

Mutagenicity

Non-hazardous by WHMIS/OSHA criteria.

Reproductive effects

Non-hazardous by WHMIS/OSHA criteria.

Teratogenicity

Hazardous by WHMIS/OSHA criteria. Toluene (benzene, methyl-) has caused fetotoxicity (reduced fetal weight), behavioral effects (effects on learning and memory) and hearing loss (in males). These effects have been observed in the offspring of rats exposed by inhalation to 1200 or 1800 ppm toluene. These effects were observed in the absence of maternal toxicity.

Synergistic Materials

Not available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Components of this product have been identified as having potential environmental concerns.

Ecotoxicity - Freshwater Algae Data

Ethyl benzene	100-41-4	72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L
Isopropanol	67-63-0	96 Hr EC50 Scenedesmus subspicatus: >1000 mg/L; 72 Hr EC50 Scenedesmus subspicatus: >1000 mg/L
Toluene	108-88-3	96 Hr EC50 Selenastrum capricornutum: >433 mg/L

Ecotoxicity - Freshwater Fish Species Data

Acetone	67-64-1	96 Hr LC50 Oncorhynchus mykiss: 4.74-6.33 ml/L; 96 Hr LC50 Pimephales promelas: 6210-8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L
---------	---------	--

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

Ethyl benzene	100-41-4	96 Hr LC50 Oncorhynchus mykiss: 11.0-18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55-11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1-15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6
Isobutyl acetate	110-19-0	48 Hr LC50 Leuciscus idus melanotus: 101 mg/L [static]; 48 Hr LC50 Leuciscus idus melanotus: 101-123 mg/L [flow-through]
Isopropanol	67-63-0	96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis crochirus:>1400000
Methyl ethyl ketone	78-93-3	96 Hr LC50 Pimephales promelas: 3130-3320 mg/L [flow-through]
Toluene	108-88-3	96 Hr LC50 Pimephales promelas: 15.22-19.05 mg/L [flow-through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89-7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1-17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static]; 96 Hr LC50 Lepomis macrochirus: 11.0-15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr LC50 Poecilia
Xylene	1330-20-7	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus Mykiss: 2.661-4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5-17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1-16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711-9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53-29.97 mg/L [static]; 96 Hr LC50 Cyprinus

Ecotoxicity - Microtox Data

Acetone	67-64-1	15 Min EC50 Photobacterium phosphoreum: 14500 mg/L
Ethyl benzene	100-41-4	30 Min EC50 Photobacterium phosphoreum: 9.68 mg/L; 24 Hr EC50 Nitrosomonas: 96
Isopropanol	67-63-0	5 Min EC50 Photobacterium phosphoreum: 35390 mg/L
Methyl ethyl ketone	78-93-3	5 Min EC50 Photobacterium phosphoreum: 3426 mg/L; 30 min EC50 Photobacterium
Toluene	108-88-3	30 Min EC50 Photobacterium phosphoreum: 19.7 mg/L
Xylene	1330-20-7	24 Hr EC50 Photobacterium phosphoreum: 0.0084 mg/L

Ecotoxicity - Water Flea Data

Acetone	67-64-1	48 Hr EC50 water flea: 0.0039 mg/L; 48 Hr EC50 water flea: 12700 mg/L [Static]; 48 Hr
Ethyl benzene	100-41-4	48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L
Isobutyl acetate	110-19-0	24 Hr EC50 Daphnia magna: 168 mg/L
Isopropanol	67-63-0	48 Hr EC50 Daphnia magna: 13299 mg/L
Methyl ethyl ketone	78-93-3	48 Hr EC50 water flea: 520 mg/L; 48 Hr EC50 Daphnia magna: 5091 mg/L
Toluene	108-88-3	48 Hr EC50 water flea: 11.3 mg/L; 48 Hr EC50 water flea: 310 mg/L; 48 Hr EC50 Daphnia magna: 11.3 mg/L
Xylene	1330-20-7	48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L

Environmental effects	Not available
Aquatic toxicity	Not available
Persistence / degradability	Not available
Bioaccumulation / accumulation	Not available
Partition coefficient	Not available
Mobility in environmental media	Not available
Chemical fate information	Not available
Other adverse effects	Not available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE CODES	Not available
DISPOSAL INSTRUCTIONS	Review federal, state/provincial, and local government requirements prior to disposal.
WASTE FROM RESIDUES / UNUSED PRODUCTS	Not available
CONTAMINATED PACKAGING	Not available

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

SECTION 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Basic shipping requirements:
Proper shipping name Paint Related Material
Hazard class 3
UN number UN128
Packing group II
Additional information:
Special provisions IB2, T7, TP1, TP8, and TP28
Packaging exceptions 150
ERG number 128



Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:
Proper shipping name Paint Related Material
Hazard class 3
UN number UN128
Packing group II
Additional information:
Special provisions 16



SECTION 15: REGULATORY INFORMATION

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Canada - WHMIS - Ingredient Disclosure List

Acetone	67-64-1	1.0 %
Ethyl benzene	100-41-4	0.1 %
Isobutyl acetate	110-19-0	1.0 %
Isopropanol	67-63-0	1.0%
Methyl ethyl ketone	78-93-3	1.0 %
Toluene	108-88-3	1.0 %

US Federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR1910.1200. All components are on the U.S. EPA TSCA Inventory List.

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Acetone	67-64-1	5000 Lb final RQ; 2270 kg final RQ
Ethyl benzene	100-41-4	1000 Lb final RQ; 454 kg final RQ
Isobutyl acetate	110-19-0	5000 Lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)
Methyl ethyl ketone	78-93-3	5000 Lb final RQ; 2270 kg final RQ
Toluene	108-88-3	1000 Lb final RQ; 454 kg final RQ
Xylene	1330-20-7	100 Lb final RQ; 45.4 kg final RQ

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Ethyl benzene	100-41-4	0.1 % de minimis concentration
Isopropanol	67-63-0	1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)
Toluene	108-88-3	1.0 % de minimis concentration
Xylene	1330-20-7	1.0 % de minimis concentration

U.S. - CWA (Clean Water Act) - Hazardous Substances

Ethyl benzene	100-41-4	Present
Isobutyl acetate	110-19-0	Present
Toluene	108-88-3	Present
Xylene	1330-20-7	Present

U.S. - CWA (Clean Water Act) - Priority Pollutants

Ethyl benzene	100-41-4	Present
Toluene	108-88-3	Present

U.S. - CWA (Clean Water Act) - Toxic Pollutants

Ethyl benzene	100-41-4	Present
Toluene	108-88-3	Present

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Benzene, ethyl-:	1000.0000
2-Butanone:	5000.0000
Benzene, methyl-:	1000.0000
2-Propanone:	5000.0000

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

Isobutyl acetate: 5000.0000
Xylene: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance - No

Section 311 hazardous chemical - Yes


Clean Air Act (CAA) Not available

Clean Water Act (CWA) Not available

WHMIS status Controlled

WHMIS classification Class B - Division 2 - Flammable Liquid, Class D - Division 2A, 2B

WHMIS labeling



State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

U.S. - California - 8 CCR Section 339 - Director's List of Hazardous Substances

Acetone	67-64-1	Present
Ethyl benzene	100-41-4	Present
Isobutyl acetate	110-19-0	Present (listed under Butyl acetate, all isomers)
Isopropanol	67-63-0	Present
Methyl ethyl ketone	78-93-3	Present
Toluene	108-88-3	Present
Xylene	1330-20-7	Present

U.S. - California - Proposition 65 - Carcinogens List

Ethyl benzene	100-41-4	carcinogen, initial date 6/11/04
---------------	----------	----------------------------------

U.S. - California - Proposition 65 - Developmental Toxicity

Toluene	108-88-3	developmental toxicity, initial date 1/1/91
---------	----------	---

U.S. - Illinois - Toxic Air Contaminants

Ethyl benzene	100-41-4	Present
Methyl ethyl ketone	78-93-3	Present
Toluene	108-88-3	Present
Xylene	1330-20-7	Present

U.S. - Louisiana - Reportable Quantity List for Pollutants

Acetone	67-64-1	5000 Lb final RQ; 2270 kg final RQ
Ethyl benzene	100-41-4	1000 Lb final RQ; 454 kg final RQ
Isobutyl acetate	110-19-0	5000 Lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)
Methyl ethyl ketone	78-93-3	5000 Lb RQ (applies to unauthorized emissions based on total mass emitted into or onto all media within any consecutive 24-hour period); 1000 lb RQ (applies to unauthorized emissions based on total mass emitted into the atmosphere).
Toluene	108-88-3	100 Lb RQ (unauthorized emissions based on total mass emitted into the atmosphere - see regulatory text for applicable parishes. The combined emission of highly reactive volatile organic compounds (acetaldehyde, butenes, ethylene, propylene, toluene, xylene, and/or isoprene) shall be totaled to determine if a RQ has been exceeded).
Xylene	1330-20-7	100 Lb final RQ; 45.4 kg final RQ (the combined emission of highly reactive volatile organic compounds (acetaldehyde, butenes, ethylene, propylene, toluene, xylene, and/or isoprene) shall be totaled to determine if a RQ has been exceeded)

U.S. - Massachusetts - Right To Know List

Acetone	67-64-1	Present
Ethyl benzene	100-41-4	Present
Isobutyl acetate	110-19-0	Present
Isopropanol	67-63-0	Present
Methyl ethyl ketone	78-93-3	Present
Toluene	108-88-3	Present
Xylene	1330-20-7	Present

U.S. - Michigan - Critical Materials List

Toluene	108-88-3	100 Lb Annual usage threshold
Xylene	1330-20-7	100 Lb Annual usage threshold (all isomers)

MATERIAL SAFETY DATA SHEET

Restor-A-Finish

MSDS DATE: 11/10/11

U.S. - Minnesota - Hazardous Substance List

Acetone	67-64-1	Present
Ethyl benzene	100-41-4	Present
Isobutyl acetate	110-19-0	Present
Isopropanol	67-63-0	Present
Methyl ethyl ketone	78-93-3	Present
Toluene	108-88-3	Skin
Xylene	1330-20-7	Present (includes all isomers)

U.S. - New Jersey - Right to Know Hazardous Substance List

Acetone	67-64-1	sn 0006
Ethyl benzene	100-41-4	sn 0851
Isobutyl acetate	110-19-0	sn 1041
Isopropanol	67-63-0	sn 1076
Methyl ethyl ketone	78-93-3	sn 1258
Propanoic acid, 2-methyl-, 2-methylpropyl ester	97-85-8	sn 1047
Toluene	108-88-3	sn 1866
Xylene	1330-20-7	sn 2014

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

Acetone	67-64-1	5000 Lb RQ (air); 1 lb RQ (land/water)
Ethyl benzene	100-41-4	1000 Lb RQ (air); 1 lb RQ (land/water)
Isobutyl acetate	110-19-0	5000 Lb RQ (air); 1 lb RQ (land/water)
Methyl ethyl ketone	78-93-3	5000 Lb RQ (air); 1 lb RQ (land/water)
Toluene	108-88-3	1000 Lb RQ (air); 1 lb RQ (land/water)
Xylene	1330-20-7	1000 Lb RQ (air); 1 lb RQ (land/water)

U.S. - North Carolina - Control of Toxic Air Pollutants

Methyl ethyl ketone	78-93-3	3.7 mg/m3 (chronic toxicants); 88.5 mg/m3 (acute irritants)
Toluene	108-88-3	4.7 mg/m3 (chronic toxicants); 56 mg/m3 (acute irritants)
Xylene	1330-20-7	2.7 mg/m3 (chronic toxicants); 65 mg/m3 (acute irritants)

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone	67-64-1	Environmental hazard
Ethyl benzene	100-41-4	Environmental hazard
Isobutyl acetate	110-19-0	Environmental hazard
Isopropanol	67-63-0	Environmental hazard
Methyl ethyl ketone	78-93-3	Environmental hazard
Toluene	108-88-3	Environmental hazard
Xylene	1330-20-7	Environmental hazard

U.S. - Rhode Island - Hazardous Substance List

Acetone	67-64-1	Toxic; Flammable
Ethyl benzene	100-41-4	Toxic; Flammable
Isobutyl acetate	110-19-0	Toxic; Flammable
Isopropanol	67-63-0	Toxic; Flammable
Methyl ethyl ketone	78-93-3	Toxic; Flammable
Toluene	108-88-3	Toxic (skin); Flammable (skin)
Xylene	1330-20-7	Toxic (skin); Flammable (skin)

Inventory name

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: OTHER INFORMATION

Disclaimer Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages that may result from the use of or reliance on any information contained in this document.

Issue date 18-May-2011

Effective date 10-Nov-2011

Expiry date 10-Nov-2014