

SAFETY DATA SHEET

1. Identification

Product identifier Chalk-Tique Dark Wax

Other means of identification Not available.

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Howard Products Inc.
Address 560 Linne Road

Paso Robles, CA 93446

United States

Telephone 1-805-227-1000 **E-mail** Not available.

Emergency phone number CHEMTREC: 1-800-424-9300

2. Hazards Identification

Physical hazardsFlammable liquidsCategory 4Health hazardsSensitization, skinCategory 1CarcinogenicityCategory 2Reproductive toxicityCategory 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. May cause an allergic skin reaction. Suspected of causing cancer. Suspected

of damaging fertility or the unborn child.

Precautionary statement

Prevention Do not handle until all safety precautions have been read and understood. Obtain special

instructions before use. Keep away from flames and hot surfaces-No smoking. Wear protective gloves, protective clothing, eye protection and face protection. Avoid breathing vapors.

Contaminated work clothing must not be allowed out of the workplace.

Response In case of fire: Use appropriate media to extinguish.

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical attention.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

Hazard(s) not otherwise

classified (HNOC)

None.

Supplemental information None.

3. Composition/Information on Ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
2-Propanol, 1-butoxy-		5131-66-8	1-5*
Cumene		98-82-8	0.1-1*
Distillates (petroleum), light hydrotreated		64742-47-8	45-70*
d-Limonene		5989-27-5	1-5*

#32324 Page: 1 of 10 Issue date 23-November-2020

Chemical name	Common name and synonyms	CAS number	%
Oils, orange, sweet		8008-57-9	0.1-1*
Paraffin wax		8002-74-2	10-30*
Solvent naphtha (petroleum), light aromatic		64742-95-6	0.5-1.5*
Xylene		1330-20-7	0.1-1*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Skin contact

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific

treatment (see information on this label). Wash contaminated clothing before reuse.

Eye contact

Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical

attention if irritation persists.

Ingestion

Rinse mouth. Drink plenty of water. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.

Most important symptoms/effects, acute and delayed

Headache. Nausea, vomiting. Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media

Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water Fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

#32324 Page: 2 of 10 Issue date 23-November-2020

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. All equipment used when handling the product must be grounded. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use appropriate container to avoid environmental contamination. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Use appropriate container to avoid environmental contamination. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

US. OSHA Table Z-1 Limits for Air Components	Type	Value	
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
Cumene (CAS 98-82-8)	TWA	50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	Form
Cumene (CAS 98-82-8)	TWA	245 mg/m3 50 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
Xylene (CAS 1330-20-7)	STEL	655 mg/m3 150 ppm	
	TWA	435 mg/m3 100 ppm	

#32324 Page: 3 of 10 Issue date 23-November-2020

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
d-Limonene (CAS 5989-27-5)	TWA	165.5 mg/m3	
0000 2. 0)		30 mag	

Biological limit values

ACGIH Biological Ex	posure Indices
---------------------	----------------

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety goggles or glasses.

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first.

Other As required by employer code. Use of an impervious apron is recommended.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with the skin and the eyes. When using do not eat or drink.

9. Physical and Chemical Properties

AppearancePaste.Physical stateLiquid.FormPaste

Color Not available.

Odor Citrus

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point and boilingNot available.

range

Pour pointNot available.Specific gravityNot available.Partition coefficientNot available.

(n-octanol/water)

Flash point 148.1 °F (64.5 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%)

Not available.

Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available. Relative density Not available. Solubility(ies) **Auto-ignition temperature** Not available.

Decomposition temperature

Not available. Not available.

Other information

Viscosity

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing.

10. Stability and Reactivity

This product may react with strong oxidizing agents. Reactivity

Possibility of hazardous

No dangerous reaction known under conditions of normal use.

reactions

Chemical stability Risk of ignition.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix

with other chemicals.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

May include and are not limited to: Oxides of nitrogen. Oxides of carbon.

11. Toxicological Information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation. Ingestion May cause stomach distress, nausea or vomiting.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Nausea, vomiting. Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Contains a potential skin sensitizer.

Components **Test Results**

2-Propanol, 1-butoxy- (CAS 5131-66-8)

Acute

Dermal

LD50 Rat > 2000 mg/kg, 24 Hours, ECHA Inhalation

LC50 Rat > 651 ppm, 4 Hours, ECHA

Oral LD50

Rat 3300 mg/kg, ECHA

Cumene (CAS 98-82-8)

Acute

Dermal

LD50 Rabbit > 3160 mg/kg, 24 Hours, ECHA

Inhalation

LC50 Rat 22.1 mg/L, 1 hr, ECHA

Oral

LD50 Rat 2260 mg/kg, ECHA

#32324 Page: 5 of 10 Issue date 23-November-2020

Components	Species	Test Results
Distillates (petroleum), light hy	drotreated (CAS 64742-47-8)	
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
	Nappit	> 2000 Hig/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Rat	> 5.3 mg/L, 4 Hours, ECHA
	Nat	> 5.5 mg/L, 4 mours, EcmA
<i>Oral</i> LD50	Rat	> 5000 mg/kg, ECHA
	Nat	> 3000 Hig/kg, EGHA
-Limonene (CAS 5989-27-5)		
Acute Dermal		
LD50	Rabbit	>= 5000 mg/kg, ECHA
Inhalation	Rabbit	7 = 3000 mg/kg, LOTIA
Innaiation LC50	Not available	
	Not available	
Oral LD50	Det	> 2000 malka FOHA
LD50	Rat	> 2000 mg/kg, ECHA
Dils, orange, sweet (CAS 8008	3-5 <i>(</i> -9)	
Acute		
<i>Dermal</i> LD50	Pat	> 5000 ma/ka FOUA
	Rat	> 5000 mg/kg, ECHA
Inhalation	Not ovailable	
LC50	Not available	
Oral	В.	. 5000 // 5014
LD50	Rat	> 5000 mg/kg, ECHA
araffin wax (CAS 8002-74-2)		
Acute		
Dermal	5 .	
LD50	Rat	> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Not available	
Oral		"
LD50	Rat	> 5000 mg/kg, ECHA
	ght aromatic (CAS 64742-95-6)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Rat	> 5610 mg/m3, 4 Hours, ECHA
Oral		
LD50	Rat	> 5000 mg/kg, ECHA
ylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Dobbit	12126 mg/kg, 24 Hours, ECHA
	Rabbit	
Inhalation		
	Rat	29000 mg/m³, 4 Hours, ECHA
Inhalation		
Inhalation		29000 mg/m³, 4 Hours, ECHA
Inhalation LC50		29000 mg/m³, 4 Hours, ECHA
Inhalation LC50 Oral LD50	Rat Rat	29000 mg/m³, 4 Hours, ECHA 6700 ppm, 4 Hours, ECHA 3523 mg/kg, ECHA
Inhalation LC50 Oral LD50 Skin corrosion/irritation	Rat Rat Prolonged skin contact may cause tempor	29000 mg/m³, 4 Hours, ECHA 6700 ppm, 4 Hours, ECHA 3523 mg/kg, ECHA
Inhalation LC50 Oral LD50	Rat Rat	29000 mg/m³, 4 Hours, ECHA 6700 ppm, 4 Hours, ECHA 3523 mg/kg, ECHA

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening Not available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Non-hazardous by OSHA criteria.

Carcinogenicity Suspected of causing cancer.

See below.

ACGIH Carcinogens

Xylene (CAS 1330-20-7) A4 Not classifiable as a human carcinogen.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Cumene (CAS 98-82-8) Ethylbenzene (CAS 100-41-4) Naphthalene (CAS 91-20-3)

IARC Monographs. Overall Evaluation of Carcinogenicity

Cumene (CAS 98-82-8) Volume 101 - 2B Possibly carcinogenic to humans.

d-Limonene (CAS 5989-27-5) Volume 56, Volume 73 - 3 Not classifiable as to carcinogenicity to

numans.

Solvent naphtha (petroleum), light aromatic (CAS

64742-95-6)

Xylene (CAS 1330-20-7) Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to

humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Cumene (CAS 98-82-8) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Repeated absorption may cause disorder of central nervous

system, liver, kidneys and blood. Prolonged exposure may cause chronic effects. Prolonged or

Volume 47 - 3 Not classifiable as to carcinogenicity to humans.

repeated exposure may cause lung injury.

Further information Symptoms may be delayed.

12. Ecological Information

See below **Ecotoxicity Ecotoxicological data Species Test Results** Components Cumene (CAS 98-82-8) Algae IC50 Algae 2.6 mg/L, 72 Hours EC50 Crustacea Daphnia 0.6 mg/L, 48 Hours Aquatic Fish LC50 Rainbow trout, donaldson trout 2.7 mg/L, 96 hours (Oncorhynchus mykiss) Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Aquatic Fish LC50 Rainbow trout, donaldson trout 2.9 mg/L, 96 hours

#32324 Page: 7 of 10 Issue date 23-November-2020

(Oncorhynchus mykiss)

Components Species Test Results

d-Limonene (CAS 5989-27-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 69.6 mg/L, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/L, 96 hours

Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)

Crustacea EC50 Daphnia 6.14 mg/L, 48 Hours

Xylene (CAS 1330-20-7)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/L, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Cumene
 3.66

 d-Limonene
 4.57

Mobility in soilNo data available.Mobility in generalNot available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport Information

General DOT - 49 CFR 173.150 (f) - Combustible Liquid Exemption

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number NA1993

Proper shipping name Combustible liquid, n.o.s.

Hazard class 3
Packing group III

Special provisions 148, IB3, T1, TP1

DOT



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) Listed.

Xylene (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely No

hazardous substance

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories Respiratory or skin sensitization

Carcinogenicity
Reproductive toxicity

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 Cumene
 98-82-8
 0.1-1*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Not regulated.

Administration (FDA)

US state regulations See below

US - Illinois Chemical Safety Act: Listed substance

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

US - Louisiana Spill Reporting: Listed substance

Cumene (CAS 98-82-8) Listed.

Xylene (CAS 1330-20-7) Listed.

US - Michigan Critical Materials Register: Parameter number

Xylene (CAS 1330-20-7) XYLENE (ALL ISOMERS)

US - Minnesota Haz Subs: Listed substance

Cumene (CAS 98-82-8) CUMENE

Paraffin wax (CAS 8002-74-2) PARAFFIN WAX FUME

Xylene (CAS 1330-20-7) DIMETHYLBENZENE (SEE XYLENE)

XYLENE (O-M-P-ISOMERS)

US - North Carolina Toxic Air Pollutants: Listed substance

Xylene (CAS 1330-20-7)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Cumene (CAS 98-82-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Paraffin wax (CAS 8002-74-2) Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Cumene (CAS 98-82-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Paraffin wax (CAS 8002-74-2) Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Cumene (CAS 98-82-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Paraffin wax (CAS 8002-74-2)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Cumene (CAS 98-82-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

#32324 Page: 9 of 10 Issue date 23-November-2020

Paraffin wax (CAS 8002-74-2) Xylene (CAS 1330-20-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Cumene (CAS 98-82-8) Listed: April 6, 2010 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 Naphthalene (CAS 91-20-3) Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Country(s) or region Inventory name On inventory (yes/no)*


United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other Information







Yes

Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 23-November-2020

Version #

Further information Not available.

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021

#32324 Page: 10 of 10 Issue date 23-November-2020